

# REEL FLP 300/36-310

02 Spools with conical flanges



Reusable

Material : ABS

Standard winding volume : 15400 cm<sup>3</sup>

Central bore Ø : 36 mm

Catalogue categorization: 02

## TECHNICAL DATA - SPOOLS

### Spools

| Flange Ø | Barrel Ø | Central bore Ø | Width   | Winding width | Flange thickness | Winding-volume       | Central bore Ø tapered part | Drive-hole/pin | Drive-distance |
|----------|----------|----------------|---------|---------------|------------------|----------------------|-----------------------------|----------------|----------------|
| d1 [mm]  | d2 [mm]  | d3 [mm]        | L1 [mm] | L2 [mm]       | S [mm]           | V [cm <sup>3</sup> ] | d4 [mm]                     | d5 [mm]        | E1 [mm]        |
| 300      | 112      | 36             | 310     | 125           | 92.5             | 15400                |                             |                |                |

## PACKAGING

| Designation         | Cardboard box | Cardboard box weight | Cardboard box Outside Deminsions | Pallets | Pallet weight | Pallet's external dimensions |
|---------------------|---------------|----------------------|----------------------------------|---------|---------------|------------------------------|
|                     | piece         | kg                   | cm                               | piece   | kg            | cm                           |
| Reel FLP 300/36-310 | 0             | -                    |                                  | 96      | 168           | 120x120x205                  |

| Designation | Cardboard box | Cardboard box weight | Cardboard box Outside Deminsions | Pallets | Pallet weight | Pallet's external dimensions |
|-------------|---------------|----------------------|----------------------------------|---------|---------------|------------------------------|
|             | piece         | kg                   | cm                               | piece   | kg            | cm                           |

**Important:**

If pallet packaging is indicated, this is the preferred method of packing the spools. Please note that the pallets must not be stored in direct sunlight, as the heat build-up may cause the plastic to warp permanently.

## TECHNICAL DRAWING

### Spools

