

# REEL K 200

03 Cylindrical barrelled delivery spools IEC 60264-2-1



Reusable

Winding material : EDM WIRE, Staple wire, Enamelled copper wire, Alloy wires, Stranded wires, Low carbon wires, Steel cord, Steel wire rope, Metal strip, metal tape

Material : PS, ABS

Standard winding volume : 3063 cm<sup>3</sup>

Central bore Ø : 22 mm

Catalogue categorization: 03

DIN EN 60264-2-1 Cylindrically barrelled delivery spools - Dimensions

DIN EN 60264-2-2 Reusable spool with cylindrically barrelled delivery - Spezifikation

## TECHNICAL DATA - SPOOLS

### Spools

Flange Ø	Barrel Ø	Central bore Ø	Width	Winding width	Flange thickness	Winding-volume	Central bore Ø tapered part	Drive-hole/pin	Drive-distance
d1 [mm]	d2 [mm]	d3 [mm]	L1 [mm]	L2 [mm]	S [mm]	V [cm <sup>3</sup> ]	d4 [mm]	d5 [mm]	E1 [mm]
200	125	16 - 22	200	160	20	3063	34	2x13	32

## PACKAGING

Designation	Cardboard box	Cardboard box weight	Cardboard box Outside Deminsions	Pallets	Pallet weight	Pallet's external dimensions
	piece	kg	cm	piece	kg	cm
Reel K 200	30	20.3	66x54x67	336	216	110x120x185

**Important:**

If pallet packaging is indicated, this is the preferred method of packing the spools. Please note that the pallets must not be stored in direct sunlight, as the heat build-up may cause the plastic to warp permanently.

## TECHNICAL DRAWING

### Spools

