

REEL DWF 500

03 Cylindrical barrelled delivery spools IEC 60264-2-1



Reusable

Winding material : bare wires, Enamelled copper wire, Alloy wires, Stranded wires, Steel wire rope, Resistance wire, Conductor, Metal strip, metal tape, superconductor, square wire

Material : ABS, PS

Standard winding volume : 21315 cm³

Central bore Ø : 36 mm

Catalogue categorization: 03

DIN EN 60264-2-1 Cylindrically barrelled delivery spools - Dimensions

DIN EN 60264-2-2 Reusable spool with cylindrically barrelled delivery - Spezifikation

TECHNICAL DATA - SPOOLS

Spools

Flange Ø	Barrel Ø	Central bore Ø	Width	Winding width	Flange thickness	Winding-volume	Central bore Ø tapered part	Drive-hole/pin	Drive-distance
d1 [mm]	d2 [mm]	d3 [mm]	L1 [mm]	L2 [mm]	S [mm]	V [cm ³]	d4 [mm]	d5 [mm]	E1 [mm]
500	315	36	250	180	35	21315	60	2 x 26	80

PACKAGING

Designation	Cardboard box	Cardboard box weight	Cardboard box Outside Deminsions	Pallets	Pallet weight	Pallet's external dimensions
	piece	kg	cm	piece	kg	cm
Reel DWF 500	3	25.1	77x52x53	39	320	100x120x215

Important:

If pallet packaging is indicated, this is the preferred method of packing the spools. Please note that the pallets must not be stored in direct sunlight, as the heat build-up may cause the plastic to warp permanently.

TECHNICAL DRAWING

Spools

