


REEL MK 200

04 Cylindrically barrelled delivery spools



Reusable

Winding material : Enamelled copper wire, Alloy wires, monofilaments

Material : PS, ABS

Standard winding volume : 3063 cm³

Central bore Ø : 22 mm

Catalogue categorization: 04

DIN EN 60264-2-1 Cylindrically barrelled delivery spools - Dimensions

TECHNICAL DATA - SPOOLS

Spools

Flange Ø	Barrel Ø	Central bore Ø	Width	Winding width	Flange thickness	Winding- volume	Central bore Ø tapered part	Drive- hole/pin	Drive- distance
d1 [mm]	d2 [mm]	d3 [mm]	L1 [mm]	L2 [mm]	S [mm]	V [cm ³]	d4 [mm]	d5 [mm]	E1 [mm]
200	125	22	200	160	20	3063	34	2x13	32

PACKAGING

Designation	Cardboard box	Cardboard box weight	Cardboard box Outside Dimensions	Pallets	Pallet weight	Pallet's external dimensions
-------------	------------------	-------------------------	--	---------	------------------	---------------------------------

Designation	Cardboard box	Cardboard box weight	Cardboard box Outside Deminsions	Pallets	Pallet weight	Pallet's external dimensions
-------------	---------------	----------------------	----------------------------------	---------	---------------	------------------------------

	piece	kg	cm	piece	kg	cm
Reel MK 200	30	29.3	66x54x67	420	392	100x120x220

Important:

If pallet packaging is indicated, this is the preferred method of packing the spools. Please note that the pallets must not be stored in direct sunlight, as the heat build-up may cause the plastic to warp permanently.

TECHNICAL DRAWING

Spools

