

REEL DWF 500/127-350

04 Cylindrically barrelled delivery spools



Reusable

Winding material : bare wires, Stainless steel wires, Enamelled copper wire, Alloy wires, Stranded wires

Material : ABS, PS

Standard winding volume : 33157 cm³

Central bore Ø : 127 mm

Catalogue categorization: 04

DIN EN 60264-2-1 Cylindrically barrelled delivery spools - Dimensions

TECHNICAL DATA - SPOOLS

Spools

Flange Ø	Barrel Ø	Central bore Ø	Width	Winding width	Flange thickness	Winding-volume	Central bore Ø tapered part	Drive-hole/pin	Drive-distance
d1 [mm]	d2 [mm]	d3 [mm]	L1 [mm]	L2 [mm]	S [mm]	V [cm ³]	d4 [mm]	d5 [mm]	E1 [mm]
500	315	127	350	280	35	33157		2 x 26	80

PACKAGING

Designation	Cardboard box	Cardboard box weight	Cardboard box Outside Deminsions	Pallets	Pallet weight	Pallet's external dimensions
-------------	---------------	----------------------	----------------------------------	---------	---------------	------------------------------

Designation	Cardboard box	Cardboard box weight	Cardboard box Outside Deminsions	Pallets	Pallet weight	Pallet's external dimensions
-------------	---------------	----------------------	----------------------------------	---------	---------------	------------------------------

	piece	kg	cm	piece	kg	cm
Reel DWF 500/127-350	2	19.5	77x52x53	25	232	100x120x197

Important:

If pallet packaging is indicated, this is the preferred method of packing the spools. Please note that the pallets must not be stored in direct sunlight, as the heat build-up may cause the plastic to warp permanently.

TECHNICAL DRAWING

Spools

