

## REEL VM 630/127-430

07 General reels, 09 VM - reels



Reusable

Winding material : data cable, power cables, Extruded cables

Material : ABS

Standard winding volume : 88841 cm<sup>3</sup>

Central bore Ø : 127 mm

Catalogue categorization: 07 , 09

DIN 46395

## TECHNICAL DATA - SPOOLS

### Spools

| Flange Ø | Barrel Ø | Central bore Ø | Width   | Winding width | Flange thickness | Winding-<br>volume   | Central bore Ø<br>tapered part | Drive-<br>hole/pin | Drive-<br>distance |
|----------|----------|----------------|---------|---------------|------------------|----------------------|--------------------------------|--------------------|--------------------|
| d1 [mm]  | d2 [mm]  | d3 [mm]        | L1 [mm] | L2 [mm]       | S [mm]           | V [cm <sup>3</sup> ] | d4 [mm]                        | d5 [mm]            | E1 [mm]            |
| 630      | 315      | 16 - 127       | 430     | 50 - 425      | 25               | 11690 - 99362        | 143.5                          | 1x22               | 95                 |

## PACKAGING

| Designation | Cardboard<br>box | Cardboard<br>box weight | Cardboard box<br>Outside<br>Deminsions | Pallets | Pallet<br>weight | Pallet's external<br>dimensions |
|-------------|------------------|-------------------------|----------------------------------------|---------|------------------|---------------------------------|
|-------------|------------------|-------------------------|----------------------------------------|---------|------------------|---------------------------------|

| Designation | Cardboard box | Cardboard box weight | Cardboard box Outside Deminsions | Pallets | Pallet weight | Pallet's external dimensions |
|-------------|---------------|----------------------|----------------------------------|---------|---------------|------------------------------|
|-------------|---------------|----------------------|----------------------------------|---------|---------------|------------------------------|

|                        | piece | kg | cm | piece | kg  | cm          |
|------------------------|-------|----|----|-------|-----|-------------|
| Reel VM<br>630/127-430 | 0     | -  |    | 16    | 189 | 120x120x192 |

**Important:**

If pallet packaging is indicated, this is the preferred method of packing the spools. Please note that the pallets must not be stored in direct sunlight, as the heat build-up may cause the plastic to warp permanently.

## TECHNICAL DRAWING

### Spools

