

# REEL VM 630/127-610

07 General reels, 09 VM - reels



Reusable

Winding material : Conductor, Metal strip, metal tape, data cable, power cables, Extruded cables

Material : ABS

Standard winding volume : 104194 cm<sup>3</sup>

Central bore Ø : 127 mm

Catalogue categorization: 07 , 09

DIN 46395

## TECHNICAL DATA - SPOOLS

### Spools

| Flange Ø | Barrel Ø | Central bore Ø | Width   | Winding width | Flange thickness | Winding-volume       | Central bore Ø tapered part | Drive-hole/pin | Drive-distance |
|----------|----------|----------------|---------|---------------|------------------|----------------------|-----------------------------|----------------|----------------|
| d1 [mm]  | d2 [mm]  | d3 [mm]        | L1 [mm] | L2 [mm]       | S [mm]           | V [cm <sup>3</sup> ] | d4 [mm]                     | d5 [mm]        | E1 [mm]        |
| 630      | 400      | 16 - 127       | 610     | 50 - 560      | 25               | 9303 - 104194        | 143.5                       |                |                |

## PACKAGING

| Designation | Cardboard box | Cardboard box weight | Cardboard box Outside Deminsions | Pallets | Pallet weight | Pallet's external dimensions |
|-------------|---------------|----------------------|----------------------------------|---------|---------------|------------------------------|
|             |               |                      |                                  |         |               |                              |

| Designation | Cardboard box | Cardboard box weight | Cardboard box Outside Deminsions | Pallets | Pallet weight | Pallet's external dimensions |
|-------------|---------------|----------------------|----------------------------------|---------|---------------|------------------------------|
|-------------|---------------|----------------------|----------------------------------|---------|---------------|------------------------------|

|                     | piece | kg | cm | piece | kg  | cm          |
|---------------------|-------|----|----|-------|-----|-------------|
| Reel VM 630/127-610 | -     | -  |    | 12    | 218 | 120x120x205 |

**Important:**

If pallet packaging is indicated, this is the preferred method of packing the spools. Please note that the pallets must not be stored in direct sunlight, as the heat build-up may cause the plastic to warp permanently.

## TECHNICAL DRAWING

### Spools

